

# RAR-24 Ring/Plus Air 24kV

Standard and versatile circuit breakers for all primary applications

## SF6-free

Perform 10000 overhaul-free mechanical operations on most ratings.

Pure air ring main unit

Have a complete range of accessories to satisfy all installation requirements.

Have a standardized range of accessories and spare parts.



Rating	Unit	Value
Rated voltage	KV	24
Rated frequency	HZ	50
Rated continuous current	A	630
Rated short-time withstand current	kA	20
Rated peak withstand current	kA	50
Rated duration of short-circuit	S	3
Rated short-time phase-to-earth withstand current	kA	20
Rated peak phase-to-earth withstand current	kA	50
Rated duration of phase-to-earth short-circuit	S	1
Filling level for insulation and/or switching (abs.)	kPa	200
Minimum functional level for insulation and/or switching (abs.)	kPa	180
Rated short-duration power-frequency withstand voltage	kV	50
Rated lightning impulse withstand voltage	kV	125
Rated Dc cable test voltage	kV	60
Rated duration for DC cable test	Min	60

Provided customized manufacture

Whole solutions for design, assembly, test...

Accountable solution for safety and reliability

Wide range offering, easy business and convenient installation

**ROCKWILL®**

Powered by [IEE Business](#)

