



B
Connection terminal
Material: Al alloy



NOTE:

- 1)、Foundation static load: 16000N
Foundation dynamic load:
horizontal direction: 5000N
vertical direction (upward): 26000N, including self weight
The height difference of the foundation shall not exceed 2mm
- 2)、The height difference of the foundation shall not exceed 2mm
The levelness of each base surface shall not exceed 2mm
- 3)、Weight: 1600KG
- 4)、Package size 1 : 2820x700x2200 (1 pcs), 1090KG;
Package size 2 : 4100x800x2300 (1 pcs), 680KG.

Anchor bolt
(Providing by client)



Main technical parameters of the product

Item	Parameter	Unit
Rated voltage	145	kV
Rated frequency	50/60	Hz
Rated current	up to 3150	A
Rated short-time withstand current, up to 3 s	40	kA
Rated peak withstand current	100	kA
Rated short-duration power-frequency withstand voltage, 1 min	275	kV
Power-frequency withstand voltage, 1 min across open contacts	275	kV
Rated lightning impulse withstand voltage, 1.2/50 μs	650	kV
Rated lightning impulse withstand voltage, 1.2/30 μs, across open contacts	650	kV
Rated filling pressure (abs. at 20 °C) circuit-breaker	0.6	Mpa
Minimum functional pressure (abs. at 20 °C) circuit-breaker	0.5	Mpa
Temperature range (ambient)	-40...+40	°C
Type of installation	outdoor	
Partial discharge capacity	<5	PC
SP6 Leakage rate per year	<0.5%	
Maintenance cycle	30	Year

DESIGNING IS SUBMITTED TO/PROE

DESIGNED BY: APPROVED BY:

CHECKED BY: APPROVED V. CHANGES:

DRAWN BY: DATE:

SCALE:

DATE:

FILE:

PAGE:

TOTAL PAGE:



PRODUCT:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145

REVISION

NO.

DATE:

FILE:

PAGE:

TOTAL PAGE:

DESIGNED BY:

CHECKED BY:

APPROVED BY:

DATE:

SCALE:

FILE:

PAGE:

TOTAL PAGE:

RHB-145