



Main Parameters :

- 1): 38kV 630A 50Hz Vacuum Auto Recloser;
- 2): STC: 20kA/3s
- 3): BIL 170kV
- 4): With 3pcs in-built CT (400/1A)
- 5): With 3pcs voltage sensor
- 6): With controller and control cable 7m
- 7): With operation counter
- 8): Clearance between Phase to phase: >377mm
- 9): Clearance between phase to earth : >401mm
- 10): Mechanism operation voltage: DC220V
- 11): Control voltage: DC24V
- 12): Operation sequence: 0-0.3s-C0-180s-C0
- 13): The creepage distance of fracture is 1295mm, and creepage distance(phase to earth) :1280mm
- 14): IEC standard: IEC62271-111

REVISION IS SUBMITTED TO/DATE:

APPROVED BY:	REVISION NO.:	DATE:
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

WENZHOUI ROCKWILL ELECTRIC CO. LTD.

PROJECT: _____

APPROVED BY: _____

SCALE: _____

Size for RCM-F38N/630-20

DATE : 01/4/2025

Page 1: Total 1 pages

DRAM : _____

DESIGNED BY: _____

APPROVED: _____

SCALE: _____

DWG. NO. _____

SHEET NO. 1

CONT. NO. 1