







Main Parameters :

1):24kV 630A 50Hz Vacuum Auto Recloser;
2):STC: 20kA/3s
3):BIL 125kV
4):With 3pcs in-built CT (400/1A)
5):With 3pcs voltage sensor
6):With controller and control cable 7m
7):With operation counter
8):Clearance between Phase to phase:>302mm
9):Clearance between phase to earth :>272mm
10):Mechanism operation voltage: DC220V
11):Control voltage: DC24V
12):Operation sequence: 0-0.3s-CO-180s-CO
13):The creepage distance of fracture is 885mm, and creepage distance(phase to earth) :774mm
14):IEC standard: IEC62271-111

DRAWING IS SUBMITTED TO/FOR:
SUBMITTED BY:
☐ FOR APPROVAL ☐ REVISION
☐ APPROVED w/ COMMENTS ☒ FOR PRODUCTION
☒ APPROVED ☐ AS-BUILT
RECEIVED BY: DATE:

WENZHOU ROCKWILL ELECTRIC CO.LTD.

PROJECT:

APPROVED BY:

TITLE: Size for RCW-F24N/630-20

REVISION: 01

DRAWN :
DESIGNED & CHECKED BY:
APPROVED:
DATE : 0114/2026

SCALE:

DWG. NO.
Page 1; Total 1 pages

SHEET NO. 1
CONT. NO. 1

THIS DOCUMENT REMAINS THE EXCLUSIVE PROPERTY OF ROCKWILL LTD. REPRODUCTION OR ANY USE NOT IN CONFORMITY WITH THE INTENDED APPLICATION IS NOT PERMISSIBLE.